DASCOM®

1225

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

Highlights at a glance:

- **Compact 24-pin wide carriage printer**
- **Up to 375 characters per second**
- **Ideal for front and back office applications**
- **Auto switching USB and parallel interface**
- **Long life ribbon**

Tally **DASCOM®**

The Tally Dascom 1225 is a 24 pin, 136 column serial dot matrix printer with USB and parallel interfaces as standard. The wide carriage printer is perfect for industrial environments and front and back office applications.

With low running costs, high quality output and an easy to use control panel it's ideal for low volume listing reports, invoices and other critical documents, as well as dispatch notes and labels.

In addition to these applications, the 1225 is also well suited for measurement and control systems. Amongst the lowest priced matrix printers available today the 1225 also offers a long life ribbon which means fewer ribbon changes, less downtime and lower running costs.

Configurations:
- **1225**   Standard Product

1225

Print Speed	375 cps (Fastest Draft); 250 cps (Draft), 83 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	336 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead Life	400 million strokes
Memory	48 kB
Standard Connectivity	Parallel (Bi-directional) and USB 2.0
Standard Emulation	IBM ProPrinter2390 Plus, Epson LQ (ESC P/2)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
Consumables	Ribbon: 7 million characters
Standard Paper Handling	Push tractor and friction
Number of Copies	1 original + 4 copies
Paper Type	Cut sheets, continuous forms, mulit-part forms
Paper Weight	52 - 100 g/m²
Paper Size	Width: 76 to 420 mm
Physical Weight	8,5 kg
Physical Size	587 x 333 x 173 mm (H x W x D)
Acoustic	55 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	7,6 Watt Stand-by
Temperature	+5° to +40° C; 10% to 80% humidity
Workload	6.000 pages per month
MTBF	10.000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS