

# LA550N, LA550W



*Tally*

The dependable LA550N and LA550W offer class-leading performance. Flat push tractors drive forms through a straight paper path, resulting in delivery of invoices, shipping bills, labels, and statements time after time.

At up to 750 characters per second and with workloads to 26,000 pages per month, the LA550N and LA550W are ideal for tough, transaction printing. The LA550N and LA550W can be optionally configured with up to three input tractors.

## Highlights at a glance:

- Print speeds up to 900 cps
- Full range of automatic features minimising operator intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel, Serial and Ethernet interfaces standard
- Includes DEC PPL2 command set and MMJ Adapter

From the small 80-column footprint of the LA550N to the 136-column capacity of the LA550W, their rugged design and quiet operation equip them for the warehouse, the shipping dock or the front desk.

Back room durability combined with front-office 24-wire print quality and a variety of automated performance features make the LA550N and LA550W a serious solution for demand document pricing.

## Configurations:

- **LA550N** 80 columns
- **LA550W** 136 columns

# LA550N, LA550W

<b>Print Speed</b>	750 cps (Fastest Draft); 500 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	446 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	400 million characters
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Serial RS-232
<b>Optional Connectivity</b>	Ethernet 10/100BaseT
<b>Standard Emulation</b>	DEC ANSI PPL2, IBM ProPrinter XL24, Epson LQ (ESC/P2)
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and large character printing
<b>Consumables</b>	Ribbon: 3,5 (LA550N) or 5 (LA550W) million characters
<b>Standard Paper Handling</b>	Push tractor and friction (front), continuous paper with straight paper path, cut sheet front insertion, tear off and park position
<b>Number of Copies</b>	1 original + 5 copies;
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 to 254 mm; Length: 76 to 599 mm (LA550N) Width: 76 to 420 mm; Length: 76 to 599 mm (LA550W)
<b>Physical Weight</b>	10,5 kg (LA550N) 13,2 kg (LA550W)
<b>Physical Size</b>	460 x 300 x 295 mm (W x D x H) (LA550N) 600 x 300 x 295 mm (W x D x H) (LA550W)
<b>Acoustic</b>	53 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	40 Watt Printing; <10 W Sleep Mode
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity
<b>Workload</b>	26.000 pages per month
<b>MTBF</b>	20.000 hours

The Printer Place  
800-243-3338  
2221 South Dupont Drive  
Anaheim, CA 92806

[www.theprinterplace.com](http://www.theprinterplace.com)

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS