

LA800+



Tally

The LA800+ is undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in its respective speed segments. It is not just 'sprinter', reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

Highlights at a glance:

- Print speeds up to 1000 cps
- Full range of automatic features minimising operator intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel, Serial and Ethernet interfaces standard
- Includes DEC PPL2 command set and MMJ Adapter

The products are well matched to Microsoft Windows applications and entirely suited to other host operating environments, including legacy systems.

DEC compatible printers continue to be in demand. These printers are particularly suited to DEC Servers, DEC VAX and Alpha, in VMS and OpenVMS operating environments. They compliment the existing entry level LA-matrix printers, the LA48N and LA48W. The products fully support the DEC ANSI PPL2 (Printer Protocol Level 2) command language (including barcodes), plus IBM Proprinter and Epson SEC P/2 for full system compatibility.

Configurations:

- **LA800+** Standard Product

LA800+

Print Speed	1.000 cps (Fastest Draft); 650 cps (Draft), 111 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	626 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/100BaseT
Optional Connectivity	Ethernet Multiprotocol
Standard Emulation	DEC ANSI PPL2, IBM ProPrinter XL24, Epson LQ (ESC P/2)
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and large character printing
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front)
Number of Copies	1 original + 6 copies
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 420 mm; Length: 76 to 559 mm
Physical Weight	19 kg
Physical Size	624 x 432 x 280 mm (W x D x H)
Acoustic	57 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	75 Watt Printing
Temperature	+10° to +35° C; 20% to 80% humidity
Workload	50.000 pages per month
MTBF	20.000 hours

The Printer Place
800-243-3338
2221 South Dupont Drive
Anaheim, CA 92806

www.theprinterplace.com

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS