



## ODV1D vs ODV2D

Key Differences/Similarities	ODV1	ODV2
Printer		
Verification Standard	ISO 15416 / ISO 15426	ISO 15415 / ISO 15416 / ISO 15426
Printer Support	T8 4/6/8in, T6 4/6in	T8 4in
Print Speed	2-10ips	2-8ips
Back-up and Overstrike	✓	✓
Maximum Barcodes per label	99	50
PNE/AutoID Support	✓	✓
Media Handling (T8)	Tear/Peel/Cut	Tear/Peel/Cut
Printer Footprint Impact	5.5in Longer, 6.0in Higher	1.7in Longer
Protective Cover	×	✓
Barcodes		
Minimum X-Dimension (4in)	6.6mil grade	10mil grade, 6.6mil decode
Barcode Type	1D	1D, 2D
Barcode Orientation	Picket Only	0, 90, 180, 270 deg
Barcode GPS	×	✓
Grading	✓	✓
Data Validation	×	✓
Scan Profile	✓	×
Field Calibration	Plaque	Plaque / Web Tool



T8000 ODV1D



**T8000 ODV2D with Cutter** 



T6000e ODV1D



**T8000 ODV2D With Protective Cover** 





## **Thank You**

The Printer Place the printer place.com 1-800-243-3338 sales@the printer place.com