



Benefits of Our ODV-2D Printers





Eliminate expensive compliance fees by producing 100% accurate barcodes, 100% of the time.

The ODV-2D is the industry's first affordable, fully integrated solution with the ability to print, verify, and validate 1D and 2D barcodes. The ODV-2D installs on either the T8000 or T6000e printers. It is the first system that grades barcodes to ISO 15415,15416 and 15426 standards and stores a detailed report of each transaction. Our exclusive technology reads each barcode, identifies a rejected barcode, and reprints a replacement label without operator intervention.

The ODV-2D pays for itself by eliminating costly charge backs and fines for non-conforming labels. Advanced features allow it to integrate easily and quickly into existing applications.



Compliant Verification

- Verifies full suite of 1D and 2D barcodes with up to 50 barcodes per label
- Performs both data validation and compliance verification
- Grades to ISO standards including Quiet Zone and Check Sum errors
- Label back up and overstrike to identify bad barcodes
- Barcode "GPS" dynamically locates barcodes on a label by label basis to improve throughput



Productivity

- Prints and verifies at up to 8 ips ODV-2D can read 1D and 2D barcodes in any 90° orientation
- Print, verify, and encode RFID labels all in a single pass, exclusively on the T6000e series
- PrintNet Enterprise Auto ID provides global or enterprise wide network access, control, update and reporting
- Compatible with third party label software through the PXML data reporting schema
- Most extensive suite of printer emulations in the industry



Dependable Design

- Field kits available for both T6000e 4" and T8000 4" and 6" printers
- Easy installation and setup
- Calibration check from printer's control panel using provided plaque
- Works with a wide variety of label and ribbon types

Frustrated by Rejected Shipments and Non-Compliance Fees?

With a global increase in regulatory compliance standards and fines, it is more important than ever to ensure your products are labeled correctly with accurate barcodes. ODV-2D addresses these requirements with the ability to validate and verify up to 50 barcodes per label including 2D barcodes.

The ODV-2D reads and grades every barcode on every label based on ISO standards. When ODV-2D rejects a barcode, it overstrikes the label and reprints it without operator intervention. At the end of the day you can generate a report directly from the printer with data on every label printed and graded.

Combining Verification with Validation

The ODV-2D can verify and validate barcodes as they are printed. The data printed on the label is validated to match the data sent from the host (native commands only). The barcode image is verified to comply with the ISO standards.

Print, Verify, and Encode RFID Labels All in A Single Pass

The upgraded T6000e with ODV-2D allows users to print and encode RFID labels and inspect and grade the quality of printed barcodes in a single pass. Now, one printer can now do the work of multiple devices to create a new level of productivity and cost savings. No longer are two separate machines needed to perform two completely different functions. This is a unique function not available on any other printer currently on the market.

| Conjugate | Conj

Full Overstrike Example

Manage Your Entire Enterprise from a Single Location

Printronix Auto ID Data Manager (part of the PrintNet Enterprise Suite) gives you the ability to dynamically record, archive and generate reports of scanned barcode data for every printer on your network. With the addition of our robust printer management tool, you can pull reports for your entire enterprise as well as monitor and configure printers from anywhere in the world. You can also designate events and be alerted to printer issues via email. PrintNet Enterprise is available at no charge.

Closed-Loop Application Design

Printronix Auto ID's integration of ODV into the printer not only enables the printer to backup and overstrike bad labels without operator intervention, but provides the application access to the data from the ODV, including grading reports as well as label images. Data from ODV can be passed back to the application in .csv or PXML format, enabling the label software to not only send labels to the printer, but can check each label to ensure that the correct data was printed and the label barcodes grades were acceptable. This data can be captured, merged with the print job information, and an image of the label can be captured as well and also archived with the ODV grading report for future reference.

Software partners such as TEKLYNX already use this application connection to provide a close-loop label quality process.



ODV-2D Series | Data Sheet







Print Width - Hax	Model	T8000 4" ODV-2D	T8000 6" ODV-2D	T6000e 4" ODV-2D
Print Resolution (dpi) 203/300 203/300 203/300 203/300/600	Print Speed - Max (ips)	8	8	8
Back-up and Overstrike Distance 6" 6" 6" 6" 6" 6" 6" 6	Print Width - Max	4.1"	6.5″	4"
Barcode Per Label - Max	Print Resolution (dpi)	203/300	203/300	203/300/600
Maximum Label Length (in)	Back-up and Overstrike Distance	6"	6"	6"
Tear/Peel Tear/Peel Tear/Peel Tear/Peel	Barcodes Per Label - Max	50	50	50
Dual Vision / RFID function No No Yes	Maximum Label Length (in)	24	24	24
Printer Footprint (L / W / H) 22" x 11.7" x 13" 24" x 13.4" x 14.5" 22" x 10.9" x 12.3" Read Technology Camera Camera Camera Grading Standard ISO 15416, ISO 15416, ISO 15426 ISO 15416, ISO 15416, ISO 15426 ISO 15416, ISO 15416, ISO 15426 ISO 15416, ISO	Media Handling	Tear/Peel/Cut	Tear/Peel	Tear/Peel
Read Technology Camera Camera Camera Grading Standard ISO 15415, ISO 15416, ISO 15426 ISO 15415, ISO 15	Dual Vision / RFID function	No	No	Yes
Paralling Standard	Printer Footprint (L / W / H)	22" x 11.7" x 13"	24" x 13.4" x 14.5"	22" x 10.9" x 12.3"
Scan Width	Read Technology	Camera	Camera	Camera
Scan Resolution (milis	Grading Standard	ISO 15415, ISO 15416, ISO 15426	ISO 15415, ISO 15416, ISO 15426	ISO 15415, ISO 15416, ISO 15426
Minimum X-Dimension 1D (mils) 10 15 10 Barcode Support - 1D Code 39, Code 33, Code 128, UPC/EAN (and supplements), 12/5 Barcode Support - 2D Datamatrix (Square, Rectangle), PDF 417, OR Datamatrix (Square, Rectangle), PDF 417, OR Barcode GPS (Auto Barcode Find) Yes Yes Yes Parcode GPS (Auto Barcode Find) O°, 90°, 180°, 270° O°, 90°, 180°, 270° O°, 90°, 180°, 270° O°, 90°, 180°, 270° OCR Using Perceptor PTXL Using Perceptor PTXL Using Perceptor PTXL OCR Point Size OCR Point Size OCR Potts OCR Potters on demand basis OCR-B Others on demand basis	Scan Width	4.5″	6.5″	4.5″
Minimum X-Dimension 2D (mils) Barcode Support - ID Code 39, Code 39, Code 39, Code 128, UPC/EAN (and supplements), 1275 Barcode Support - 2D Datamatrix (Square, Rectangle), PDF 417, QR PVes Yes Yes Yes Yes O'c, 90°, 180°, 270° O'c, 90°, 180°,	Scan Resolution (mils)	2	3	2
Barcode Support - 1D Code 39, Code 93,	Minimum X-Dimension 1D (mils)	10	15	10
Barcode Support - 10 (and supplements), I 2/5 (Septiments), I 2/5 (And supplements), Post 4/7 (And Supplements), I 2/5 (A	Minimum X-Dimension 2D (mils)	10	15	10
Barcode GPS (Auto Barcode Find) Yes Yes Yes Yes Yes Arial, Cambria, Consolas, OCR-B Others on demand basis OCCY / Blemish Detect / Pattern Match / Duplicate Check Output Reports Yes Yes Yes Yes Yes Yes Yes Y	Barcode Support - 1D			
Barcode Orientation 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 90°, 180°, 270° 0°, 180° 0°, 180° 0°, 180° 0°, 180° 0°, 180° 0°, 180° 0°, 180	Barcode Support - 2D	Datamatrix (Square, Rectangle), PDF 417, QR	Datamatrix (Square, Rectangle), PDF 417, QR	Datamatrix (Square, Rectangle), PDF 417, QR
Using Perceptor PTXL Using Per	Barcode GPS (Auto Barcode Find)	Yes	Yes	Yes
OCR Point Size 5pt 5pt 5pt 6pt Arial, Cambria, Consolas, OCR-B Others on demand basis CCV / Blemish Detect / Pattern Match / Duplicate Check Using Perceptor PTXL Output Reports Yes Yes Yes Yes Yes PrintNet Enterprise Remote Management Yes Yes Yes Yes Yes Yes Yes Ye	Barcode Orientation	0°, 90°, 180°, 270°	0°, 90°, 180°, 270°	0°, 90°, 180°, 270°
OCR Fonts Arial, Cambria, Consolas, OCR-B Others on demand basis OCR-B Others on demand basis OCV / Blemish Detect / Pattern Match / Duplicate Check Using Perceptor PTXL Output Reports Yes Yes Yes Yes Yes PrintNet Enterprise Remote Management Yes Yes Yes Yes Yes PXML Grade Report Capture Yes N/A N/A UHF / RAIN (GS1 EPC Gen2 v2 / ISO 18000-63)	OCR	Using Perceptor PTXL	Using Perceptor PTXL	Using Perceptor PTXL
OCR-B Others on demand basis OCR-B OTHER O	OCR Point Size	5pt	5pt	6pt
Duplicate Check Using Perceptor PTXL Using Percepto	OCR Fonts	Arial, Cambria, Consolas, OCR-B Others on demand basis	Arial, Cambria, Consolas, OCR-B Others on demand basis	Arial, Cambria, Consolas, OCR-B Others on demand basis
PrintNet Enterprise Remote Management Yes Yes Yes Yes Yes Yes PXML Grade Report Capture Yes Yes Yes Yes Yes Yes Yes Yes Yes Ye	OCV / Blemish Detect / Pattern Match / Duplicate Check	Using Perceptor PTXL	Using Perceptor PTXL	Using Perceptor PTXL
Remote Management Tes Tes Data Report Capture Yes Yes PXML Grade Report Capture Yes Yes RFID Option N/A N/A UHF / RAIN (GS1 EPC Gen2 v2 / ISO 18000-63)	Output Reports	Yes	Yes	Yes
PXML Grade Report Capture Yes Yes Yes RFID Option N/A N/A UHF / RAIN (GS1 EPC Gen2 v2 / ISO 18000-63)	PrintNet Enterprise Remote Management	Yes	Yes	Yes
RFID Option N/A N/A UHF / RAIN (GS1 EPC Gen2 v2 / ISO 18000-63)	Data Report Capture	Yes	Yes	Yes
·	PXML Grade Report Capture	Yes	Yes	Yes
Cloud Database Using Perceptor PTXL Using Perceptor PTXL Using Perceptor PTXL Using Perceptor PTXL	RFID Option	N/A	N/A	UHF / RAIN (GS1 EPC Gen2 v2 / ISO 18000-63)
	Cloud Database	Using Perceptor PTXL	Using Perceptor PTXL	Using Perceptor PTXL

For more information on ODV or label quality inspection, please contact your local Printronix Auto ID sales representative.







Perceptor PTXL trademark is owned by InterVision Global Group | perceptor-ptxl.com

The Printer Place | 800-243-3338 | theprinterplace.com | service@theprinterplace.com | 2221 South Dupont Drive | Anaheim, CA 92806