

Ribbons for TTP-225 Series

- **™** Retail POS and Product Marking
- M Oil Change & Auto
- Document Management
- Inventory and Asset Management



Printer Models:

- TTP-225
- •TTP-323




Ribbons available for TSC TTP-225 Series


Supported by a full range of ink formulations, you can be confident that your Genuine TSC ribbon will meet the demands of your label printing application.

Enjoy consistent, premium quality and optimized performance through your TSC printer.

SWX - TSC Standard Wax



PWX - TSC Premium Wax




- Widely used for barcode application. Provides excellent print quality.
- Suitable for standard labeling applications
- Compatible with most coated and non-coated paper labels

Width (mm)	58
Length (m)	90
No. rolls/Box	48
Your P/N	35-W058090-24CA


- Resin-enhanced wax
- Best scratch and smudge resistance for a wax ribbon
- Supports high speed printing
- Excellent print quality on all papers and some film materials

Your P/N	35-W058090-24CB
No. rolls/Box	48
Length (m)	90
Width (mm)	58

SWR - TSC Standard Wax/Resin



PWR - TSC Premium Wax/Resin




- General purpose wax/resin formulation
- Superior print quality on all common papers and films. Our most versatile formulation.
- Good scratch and smudge resistance

Width (mm)	58
Length (m)	90
No. rolls/Box	48
Your P/N	35-S058090-24CC


- Designed to print on a wide range of coated papers and films
- Very sharp print quality, enabling ladder and rotated barcode printing simultaneously
- Enhanced abrasion and scratch resistance

Width (mm)	58
Length (m)	90
No. rolls/Box	48
Your P/N	35-S058090-24CD

SRE - TSC Standard Resin



PRE - TSC Premium Resin



- Excellent mechanical resistance, including abrasion and scratch
- Extensive adaptability to a wide range of film materials
- Supports higher print speeds

Length (m) No. rolls/Box	90 48
Your P/N	35-R058090-24CE

- Designed for the most extreme environmental conditions
- . Highest abrasion, scratch and solvent resistance
- Compatible with a wide range of synthetic materials

Your P/N	35-R058090-24CF
No. rolls/Box	48
Length (m)	90
Width (mm)	58